SCANDIC'S ACCESSIBILITY STANDARD

Here you can read our 135 point accessibility standard. It has been drawn up by carefully following the route taken by guests from the car park on through the whole hotel. We have also talked to disability organisations and guests with physical disabilities and received lots of ideas from our own keen staff. Although we rent our hotels rather than owning them, there is a lot that we can do. 90 of the 135 points are compulsory for all hotels. All 135 of the points need to be applied as we renovate or build new hotels.

The standard applies in all nine of the countries in which Scandic is represented. Of course we also have to comply with the legislation in the country concerned. This means that if the legislation in the country in question is stricter on any particular point, that takes precedence. In the cases where our standard is higher than the legislation, of course our standard applies.

Our accessibility standard doesn't include everything that we actually do on the ground. Accessibility issues are incorporated as part of our day to day work, whatever the area. This means that for example, safety issues involving accessibility are in our safety standard, signs in our signage standard, and so on. In other words accessibility issues are an important part of the whole of Scandic and everyone in our team undergoes training in them.

We describe the accessibility for each individual hotel on their respective websites. We are the only hotel chain in the world to do this.

/Magnus Berglund, Director of Accessibility Scandic Hotels

Number	ZINO 9	Guest need/expectations	Mandatory	When reconstructing New building	Remarks		
PAR	KING &	ENTRANCE			If there is parking		
1		Disabled parking, at least 2 spaces with a minimum width of 3.6 metres each.	Χ		(next to the entrance)		
2		Accessible parking must be clearly marked with the wheelchair symbol.	Χ				
3		Additional signage at parking bays "For assistance, please call reception on XXXX".	Χ				
4		Clearly signposted and illuminated wheelchair-accessible route between parking and entrance.	Χ		Wheelchair accessible.		
5		Access ramps at changes of level with a maximum gradient of 1:12 at the main entrance to the hotel and to/from the parking area.	Х				
6		Contrast markings at start and end of ramps.	Χ				
7		Main entrance door has a minimum width of 800 mm free clearance.	Χ				
8		Low or no threshold at the entrance door for easy wheelchair access.	Χ				
9		Night time door bell accessible from wheelchair, with a sign and illuminated.	Х		Height 1200 mm		
10		Entrance door provided with automatic push plate, maximum height 1200 mm.	Χ		If door is not fully automatic.		
11		Contrast marking on electric push plate, see list of explanations.	Χ				
12		Clearly signed directions if the accessible entrance is not next to the hotel's main entrance/building.	Х				
13		The recommended distance to the accessible entrance is a maximum of 25 metres from the car park.		Χ			
14		Contrast markings are required if there is an electric door opening system.	Χ				
REC	RECEPTION						
15		At least 2 cane holders attached to reception desk.	Χ				
16		Seating and tables close to reception desk.	Χ				
17		Hearing loop at reception marked with the correct sign.	Χ				



Number	Guest need/expectations	Mandatory	When reconstructing New building	Remarks
18	Vibrating wake up/fire alarm available to borrow, sign at reception.	Χ		Clear sign on reception desk.
19	Entrance carpet from entrance to reception in a different colour from flooring, or a guide line.	Χ		
20 🗌	A guide line should be provided if the reception is not immediately inside the entrance.		Χ	
21 🗌	Part of reception at a height adapted for guests in wheelchairs.		Χ	
LOBBY				
22	Reachable electric socket for charging electric wheelchairs marked with a sign.		Χ	Height 1200 mm.
23	Shop – clear aisles at least 800 mm wide. Products can be reached from a wheelchair.	Χ		
24	Clear walkway between reception and lift (for wheelchairs).	Χ		
25	Wheelchair available to borrow.		Χ	
GUEST COM	MPUTER			
26	Minimum requirement one wheelchair accessible workstation.	Х		
LIFTS				
27	Clear directions to the wheelchair accessible lift.	Х		If not all lifts are accessible.
28	Push plate to open doors (if doors are not automatic).		Χ	
29 🗌	Lift button and button panel inside the lift must be able to be reached from a wheelchair.	Χ		
30 🗆	Lift buttons and button panels must be marked in Braille. Tactile buttons in each lift and on each floor.		Χ	
31	Voice announcements for each floor and whether the lift is going up or down.		Χ	
32	The hotel must have at least one lift with a minimum door width of 800 mm.	Х		
33	Mirror inside the lift opposite lift doors so that it is possible to see when the doors open/close from a wheelchair.		Χ	
MAIN STAIF	RS (AND STAIRS BETWEEN FLOORS)			
34	First and last steps clearly marked with a different colour.	Х		Floors + landings.
35	Hand rails on both sides of the staircase (if staircase is wider than 105 cm).	Χ		
36	Hand rails at the top and bottom of the stairs must extend 300 mm on each side before the stairs start.		Χ	
37	The hand rails must be in a contrasting colour to the background.		Χ	
38	Stone or concrete stairs must be provided with a non-slip surface on the edges of the steps.		Χ	
CLOAKROC	M			
39	Some hangers/hooks must be able to be reached from a wheelchair, height 1200 mm.	Χ		
CORRIDOR	S (PATHS, WALKWAYS)			
40	Corridors to be a minimum of 1300 mm wide.	Х		
41	Other indoor areas must have at least 800 mm free clearance.		Χ	Between wall & pillar
MEETING R				
42 📙	Door openings must be at least 800 mm.		Х	
43	Meeting rooms without carpet (hard flooring). 50 % of rooms.		Χ	
44	Phones must be able to be reached from a wheelchair.	Х		
45	Coat hangers or hooks for outdoor clothing must be able to be reached from a wheelchair, height 1200 mm.		Χ	
46	Hearing loops available to borrow for meetings.	Х		
47	Permanent hearing loop in all large meeting rooms (<50 people with theatre seating).		Χ	
48	A sign stating that there is a hearing loop for meetings.	Х		
49	Whiteboard fitted at maximum lowest height of 1200 mm at the bottom edge.	Χ		



Number		Guest need/expectations	Mandatory	When reconstructing New building	Remarks
AUDITO	ORIU	M			
50		Stage – wheelchair accessible.	Χ		Maximum slope of ramp < 1:12
51		Podium – alternative with wheelchair accessibility must be available.		Χ	
52		Space for wheelchairs in the room, easily accessible.	Χ		
53		No threshold or low threshold adapted for easy wheelchair access.		Х	
BREAK	(001	AREAS			
54		Seating must be available outside meeting rooms.	Χ		
F&B, R	RESTA	AURANT AREAS			
55		Height of buffets must be 850 – 900 mm.		Х	
56		Glass, china and cutlery must be able to be reached from a wheelchair.	Χ		
57		Breakfast – special bread for people who are gluten and lactose intolerant.	Χ		
GUEST	TOII	LETS — ACCESSIBLE TOILETS			
58		Signs showing where accessible toilets are located.	Х		
59		Door width at least 800 mm free clearance.	Χ		900 mm recommended.
60		Rail on the inside of the door, under the handle.	Χ		
61		Lock with handle, see list of explanations.		Χ	
62		No threshold or low threshold adapted for easy wheelchair access.	Χ		
63 [Alarm.	Х		In line with Scandic Safety & Security Manual.
64		Mirror above washbasin must be able to be seen from a wheelchair.	Χ		
65 E		Full-length mirror on the wall.		Χ	
66		Contrast marking behind WC, see list of explanations.		Χ	
67		Waste paper bin hung on the wall, can be opened from a wheelchair.	Χ		
WASH	BASI	NS			
68		Minimum height of washbasin 780 mm.	Χ		
69		Empty surface immediately adjoining washbasin/WC.		Χ	
70		Wheelchairs must be able to fit under the washbasin.	Χ		
71		Single lever mixer taps.	Χ		
72		Accessible soap dispenser, can be reached from a wheelchair.	Χ		
73		Hand towels can be reached from a wheelchair.	Х		
74		Coat hangers/hooks can be reached from a wheelchair, height 1200 mm, and 1600 mm.	Χ		
75 E		Cane holder, x 1, height 1200 mm.		Х	
TOILET	rs				
76		Foldable armrests (when buying new, see list of explanations).	Χ		
77		Toilet paper holder on arm rest and on wall.	Χ		
DIRECT	TION	SIGNS			
78		Clearly marked in contrasting colours.	Χ		
79		At a height of 1400 – 1600 mm.		Χ	



Number	Guest need/expectations	Mandatory	When reconstructing New building	Remarks
SLEEPING -	- ACCESSIBLE ROOMS			
80	Phone can be reached from the bed.	Х		
81	TV remote control on bedside table.	Х		
82	Bed height adjustable for back and legs.		Х	
83	Extra electrical socket for electric beds on the wall below the headboard.		Х	
84	Recommended total height of bed 550 mm including mattress.	Х		
85 🗌	At least 800 mm free floor space on one side of the bed.	Χ		
86	At least 900 mm free floor space on one side of the bed, see list of explanations.		Х	Divided 50/50 right/left.
87 🗌	Lights must be able to be switched off from a wheelchair.	Χ		
MISCELLA	NEOUS – ACCESSIBLE ROOMS			
88	All accessible rooms must have a connecting door to an adjoining room.		Χ	
89 🗌	Two peepholes in the door, one at ordinary height and one at 1200 mm.	Χ		
90	Electric push plate for door (if required by the law in the country in question).		Χ	
91	Contrast marking on electric push plate, see list of explanations.	Χ		
92	If there is an electric push plate, it must be marked in a contrasting colour, see list of explanations.	Х		
93	Free clearance at doorway into room of at least 800 mm.	Χ		
94	Wardrobe must be able to be opened from a wheelchair.	Χ		
95	Hat/coat shelf, height 1200 mm.	Х		
96	Wardrobe shelf can be reached from a wheelchair.	Χ		
97	All lighting switches must be able to be reached from a wheelchair.		Х	
98	Floor lamp must be able to be turned on/off from a wheelchair.	Χ		
99	Desk – accessible in a wheelchair.	Χ		
100	Desk hung on the wall.		Х	
101	Electric socket by desk can be reached from a wheelchair.		Х	
102	Wardrobe with sliding doors or without doors.		Х	
103	Visual fire alarm.		Х	
104	Room thermostat placed so it can be reached from a wheelchair, height 1200 mm.		Х	
BATHROOM	I – ACCESSIBLE ROOMS			
105	Free clearance at doorway into room of at least 800 mm.	Χ		
106	Rail on the inside of the door, under the handle or sliding door.	Χ		
107	No threshold or low threshold adapted for easy wheelchair access.	Χ		
108	Alarm.	Х		En line with Scandic Safety & Security Manual
109	Minimum height of washbasin 780 mm.	Х		
110	Wheelchairs must be able to fit under the washbasin.	Χ		
111	Single lever mixer tap reachable from a wheelchair.	Χ		
112	One accessible soap dispenser, can be reached from a wheelchair.	Х		
113	Towels can be reached from a wheelchair.	X		



Number	Guest need/expectations	Mandatory	When reconstructing New building	Remarks
114	Coat hangers/hooks can be reached from a wheelchair, height 1200 mm, and 1600 mm	Χ		
115	Mirror above washbasin must be able to be seen from a wheelchair.	Χ		
116	If there is a make-up mirror, it must be able to be reached from a wheelchair.	Χ		
117	Hair dryer reachable from a wheelchair.	Χ		
SHOWER				
118	Accessible with a wheelchair.	Χ		
119	Thermostat tap.	Χ		
120	One shower gel/shampoo holder, can be reached from a wheelchair.	Χ		
121 🗌	Empty space (maximum height 1200 mm) for shampoo, etc.	Χ		
122	Shower stool available.	Χ		
123	Shower stool with back and arm rests compulsory with new purchasing.		Χ	
124	Towels can be reached from a wheelchair.	Χ		
125	Hooks must be provided at two heights.	Χ		
126	Shower head must be at its lowest level when guests arrive.	Χ		
127	Shower head must be fitted at a maximum lowest height of 1200 mm.		Х	
128	Shower curtain or glass shower wall.	Χ		Depending on measurements.
129	Glass shower wall.		Х	Fitted in newly built hotels, renovations or replaced where measurements allow.
130	Railings/handles must be provided in the shower.		Χ	
TOILET ARE	A			
131	Foldable arm rests.	Χ		
132	Foldable and height adjustable and removable armrests on both sides, see list of explanations.		Х	
133	Toilet paper holder on arm rest and on the wall.	Χ		
134	Contrast marking behind WC.		Χ	
135	Waste paper bin hung on the wall, can be opened from a wheelchair.		Χ	





